

Technical Specifications

RescueONE® 1673-X2™ Connector Boat®

Technical Specifications US-Metric

(Note: Bid Specs are available upon request.)

1673-X2™ Connector Boat® (Hull only)

Length 16'6" - 5.0 m

Beam 6' 3" - 1.87 m Bottom Width 60" - 1.52 m

Side Depth-Outside 21" - 53 cm

Side Depth - Inside 19" - 48 cm

Height With Motor 42" - 106 cm

Height With Light Bar Mount (not folded) 62" - 157 cm

Height With Light Bar Mount (folded) 30" - 76 cm

Interior Operating Space = 64 Sq Ft - 6.0 sq m

(with SEATool™ Boxes Removed)

Dry Weight 580 Lbs.- 262 Kg

Hull Material 0.100 thickness marine aluminum

Double Hull with 2" foam separating them

For full speed operation including emergency maneuvers:

Max Recommended Weight Capacity 1800 Lbs - 816 Kg

Max Persons Weight 1250 Lbs - 567 Kg

Max Number of Persons - 8

Max Recommended Horsepower:

-With Tiller steer outboard - 50hp

-With Remote Steer/ Console - 70hp

1673-SS Transport™ Trailer

Length 20' 2" - 6.1 m

(with SpaceSAVER™ tongue extended in towing position)

Length 17' 6" - 5.4 m

(with SpaceSAVER™ tongue folded in storage position)

Width 7' 9" - 2.3 m

Height With Motor 5' 5" - 1.6 m

Height With Light Bar Not Folded 7' 3" - 2.2 m

Height With Light Bar Folded 4' 7" - 1.4 m

GWWR 2720 Lbs - 1234 Kg

Max Weight Capacity 2000 Lbs - 907 Kg

TwinTransport™ Trailer

Length 22'5" - 6.83 m

Width 7' 9" - 2.3 m

Height (Trailer Only) 8' 4" - 2.5 m

Height With Boat On Top Rack 9' 7" - 2.9 m

Electric Winch capacity 8500 Lbs - 3855 Kg

GWWR 4250 Lbs - 1928 Kg

Max Weight Capacity 2800 Lbs - 1270 Kg

BID SPECS AVAILABLE

Assistance with preparing custom bid specifications is available. Please contact us for details.



Boat Connector Posts



Removable SEATool™ Boxes